




Roof Mounted Fan Tray

Manufactured by DPS in the UK. We design, punch, fold, powdercoat, assemble, test and despatch.

Standard Options

DC Fans	
Low Noise Fan	
Thermostat	
Speed Control	
Fan Fail	



	LOW NOISE		STANDARD FAN	
	Specification	Unit	Specification	Unit
RATED VOLTAGE	230	VAC	230	VAC
FREQUENCY	50 / 60	Hz	50 / 60	Hz
SPEED	1350 / 950	R.P.M.	2400 / 2700	R.P.M.
INPUT CURRENT	0.05 / 0.04	Amp	0.16	Amp
NOMINAL CURRENT	0.10	Amp	0.16	Amp
AIR FLOW	49.1 / 34.7	CFM	90 / 100	CFM
STATIC PRESSURE	1.34 / 0.73	mmAq	0.236 / 0.276	InchH ₂ O
NOISE	28.6 / 23.4	dBA	39 / 42	dBA
LIFE EXPECTANCY	50,000	Hours	50,000	Hours

2M lead with various plug options
 Specials made to order
 All steel construction
 Powder coated RAL7044

Data & Power Solutions Ltd.

Unit 1, The Monarch Centre, Venture Way, Priorswood, Taunton, Somerset. UK. TA2 8DE

tel: + 44(0)1823 275 100 fax: +44(0)1823 275 002

email: sales@dataandpower.com web: www.dataandpower.com

