






**Data and Power Solutions – technical information sheet**  
**Outdoor Assembly Unit Specification**

VERSIONS	
	<p><b>BLOCK 1 (110x280x95mm)</b></p> <ul style="list-style-type: none"> <li>❖ <i>Portable or surface mounting empty units</i></li> </ul>
	<p><b>BLOCK 3 (136x440x114mm)</b></p> <p><i>Installation:</i></p> <ul style="list-style-type: none"> <li>❖ <i>Surface mounting</i></li> <li>❖ <i>Panel mounting</i></li> <li>❖ <i>Mobile on appropriate stand</i></li> <li>❖ <i>Portable with cable and plug</i></li> </ul>
	<p><b>BLOCK 4 (212x415x114mm)</b></p> <p><i>Installation:</i></p> <ul style="list-style-type: none"> <li>❖ <i>Surface mounting</i></li> <li>❖ <i>Panel mounting</i></li> <li>❖ <i>Mobile on appropriate stand</i></li> <li>❖ <i>Portable with cable and plug</i></li> </ul>

REFERENCE STANDARDS
Standards: <b>IEC 60670</b> <b>EN 60439-1</b> <b>EN 60439-4</b>

MARKING
Marking: <b>CE Marking</b> 

QUALITY MARKS
 

TECHNICAL CHARACTERISTICS
Protection degree: <b>IP44-IP66</b>
Operating temperature according to the reference standard: <b>-25°C+35°C</b>
Max operating temperature: <b>60°C</b>
Glow Wire test: <b>650°C</b>
Material: <b>Engineering plastic</b>
IK degree at 20°C: <b>IK08</b>
Cable inlet: <b>PG13,5 – PG21</b>
Total isolation <input type="checkbox"/> : <b>YES</b>
Dissipable power according to CEI 23-49 standard: <b>8-14W</b>
Colour: <b>Grey RAL 7035</b>

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS										
Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
RESISTANT	LIMITED RESISTANCE	RESISTANT	LIMITED RESISTANCE	RESISTANT	NOT RESISTANT	NOT RESISTANT	NOT RESISTANT	LIMITED RESISTANCE	RESISTANT	RESISTANT